

**SGC-M156-2011**  
**EXPLUSSION PROOF PRESSURE SWITCH**

التسلسل ITEM	المواصفات DESCRIPTION	الوحدة UNIT	الكمية المطلوبة REQ.QTY
1	<b>EXPLUSSION PROOF PRESSURE SWITCH</b>  RANGE: 0 – 11 mmH <sub>2</sub> O      OR EQUIVELENT  MAXIMUM PRESSURE: 40 MH <sub>2</sub> O  DIFFRENTIAL PRESSURE: 250 mmH <sub>2</sub> O  ELECTRICAL RATING : 15A 220VAC – 0.4A 125VDC    OR EQUIVELENT  WITH TWO MICRO SWITCH  IP: 65  PROCESES CONNECTION: 1/2" NPT  ELECTRICAL CONNECTION: 1/2" NPT	NOS	20
2	<b>EXPLUSSION PROOF PRESSURE SWITCH</b>  RANGE: 0 – 100 Kg/cm <sup>2</sup> OR EQUIVELENT  MAXIMUM PRESSURE: 160 Kg/cm <sup>2</sup>  DIFFRENTIAL PRESSURE: 2Kg/cm <sup>2</sup>  ELECTRICAL RATING: 15A 220VAC – 0.5A 125VDC OR EQUIVELENT  WITH TWO MICRO SWITCH  IP: 65  PROCESES CONNECTION: 1/2" NPT  ELECTRICAL CONNECTION: 1/2" NPT	NOS	10
3	<b>EXPLUSSION PROOF PRESSURE SWITCH</b>  RANGE: 0 – 2.5 Kg/cm <sup>2</sup> OR EQUIVELENT  MAXIMUM PRESSURE: 4.5 Kg/cm <sup>2</sup>  DIFFRENTIAL PRESSURE: 0.13 Kg/cm <sup>2</sup>  ELECTRICAL RATING: 15A 220VAC – 0.5A 125VDC OR EQUIVELENT	NOS	10

	<p>WITH TWO MICRO SWITCH</p> <p>PROCESES CONNECTION: 1/4" NPT</p> <p>ELECTRICAL CONNECTION: 1/2" NPT</p>		
4	<p><b>EXPLUSSION PROOF PRESSURE SWITCH</b></p> <p>RANGE: 0 – 40 Kg/cm<sup>2</sup> OR EQUIVELENT</p> <p>MAXIMUM PRESSURE: 75 Kg/cm<sup>2</sup></p> <p>DIFFERENTIAL PRESSURE: 0.55 Kg/cm<sup>2</sup></p> <p><b>ELECTRICAL RATING: 15A 220VAC – 0.5A 125VDC OR EQUIVELENT</b></p> <p>WITH TWO MICRO SWITCH</p> <p>PROCESES CONNECTION: 1/4" NPT</p> <p>ELECTRICAL CONNECTION: 1/2" NPT</p>	NOS	10
5	<p><b>EXPLUSSION PROOF PRESSURE SWITCH</b></p> <p>RANGE: 0 – 16 Kg/cm<sup>2</sup> OR EQUIVELENT</p> <p>MAXIMUM PRESSURE: 30 Kg/cm<sup>2</sup></p> <p>DIFFERENTIAL PRESSURE: 0.23 Kg/cm<sup>2</sup></p> <p><b>ELECTRICAL RATING: 15A 220VAC – 0.5A 125VDC OR EQUIVELENT</b></p> <p>WITH TWO MICRO SWITCH</p> <p>PROCESES CONNECTION: 1/4" NPT</p> <p>ELECTRICAL CONNECTION: 1/2" NPT</p>	NOS	10
6	<p><b>EXPLUSSION PROOF DIFFERENTIAL PRESSURE SWITCH</b></p> <p>RANGE: 0 – 20 MH<sub>2</sub>O OR EQUIVELENT</p> <p>MAXIMUM PRESSURE: 100 Kg/cm<sub>2</sub></p> <p>DIFFERENTIAL PRESSURE: 750 mmH<sub>2</sub>O</p> <p><b>ELECTRICAL RATING: 15A 220VAC – 0.5A 125VDC OR EQUIVELENT</b></p> <p>WITH TWO MICRO SWITCH</p> <p>PROCESES CONNECTION: 1/2" NPT</p> <p>ELECTRICAL CONNECTION: 1/2" NPT</p>	NOS	10
7	<p><b>EXPLUSSION PROOF DIFFERENTIAL PRESSURE SWITCH</b></p> <p>RANGE: 0 – 40 MH<sub>2</sub>O OR EQUIVELENT</p> <p>MAXIMUM PRESSURE: 40 Kg/cm<sup>2</sup></p>	NOS	10

	<p>DIFFERENTIAL PRESSURE: 1700 mmH<sub>2</sub>O</p> <p>ELECTRICAL RATING: 15A 220VAC – 0.5A 125VDC OR EQUIVELENT</p> <p>WITH TWO MICRO SWITCH</p> <p>PROCESES CONNECTION: 1/4" NPT</p> <p>ELECTRICAL CONNECTION: 1/2" NPT</p>		
	<p><b>ORIGIN:</b></p> <p>USA OR West Europe</p> <p><b>NOTES:</b></p> <p>ONE YEAR WARANTY</p>		