

SGC-M160-2011

MULTIFUNCTION PROGRAMMABLE CONTROLLER

التسلسل ITEM	المواصفات DESCRIPTION	الوحدة UNIT	الكمية المطلوبة REQ.QTY
1	MULTIFUNCTION PROGRAMMABLE CONTROLLER OR Equivalent MODEL: AC30/501000/0000 THREE SET OF USB DATA CABLE BETTWEN AC – 30 & COMPUTER & ALL SOFTWARE REQRUMENT	NOS	20
2	CURRENT TO PRESSURE TRANSDUCER OR Equivalent MODEL: 3311 TYPE: 846DS1J1B2F2G8K5 AIR SUPPLY: 20 PSI INPUT SIGNAL: (4 – 20) mA OUTPUT SIGNAL: (3 – 15) PSI WITH ALL ACCESSORIES (CABLE GLAND 1/2 " , 2 " U – BOLT PIPE MOUNTING BRACKET, AIR REGULATOR & PRESSURE GAUGE)	NOS	20
3	SAFETY BARRIERS POWER SUPPLY: 24 VDC INPUT: 1 – 5 VDC OUTPUT: 4 – 20 mA	NOS	50
4	SAFETY BARRIERS POWER SUPPLY: 24 VDC INPUT: (4 – 20) mA SUPPLIED THE TRANSMITTER BY 24 VDC OUTPUT: 1 – 5 VDC	NOS	50
5	EX-PROOF SMART PRESSURE TRANSMITTER OR Equivalent MODEL: 3051 SPAN RANGE: (10 – 100) Kg /cm ² CALIBRATION RANG (0 – 100) Kg / cm ² FLUED: NATURAL GAS POWER SUPPLY: 24 VDC OUTPUT SIGNAL (4 – 20) mA PROCESS CONNECTION: 1/2 " NPTF WITH ALL ACCESSORIES (CABLE GLAND 1/2 " NPT , 2" U – BOLT PIPE	NOS	10

	MOUNTING BRACKET)		
6	<p>EX-PROOF SMART PRESSURE TRANSMITTER <i>OR Equivalent</i></p> <p>MODEL: 3051 SPAN RANGE: (2 – 17) Kg /cM²</p> <p>CALIBRATION RANG (0 – 10) Kg / cM²</p> <p>FLUED: NATURAL GAS</p> <p>POWER SUPPLY: 24 VDC</p> <p>OUTPUT SIGNAL (4 – 20) mA</p> <p>PROCESS CONNECTION: 1/2 " NPTF</p> <p>WITH ALL ACCESSORIES (CABLE GLAND 1/2 " NPT , 2" U – BOLT PIPE MOUNTING BRACKET)</p>	NOS	10
7	<p>EX-PROOF SMART DIFFERENTIAL PRESSURE TRANSMITTER <i>OR Equivalent</i></p> <p>MODEL: 3051 CD SPAN RANGE: (500 – 5000) mmH₂O</p> <p>CALIBRATION RANG (0 – 5000) mmH₂O</p> <p>FLUED: NATURAL GAS</p> <p>POWER SUPPLY: 24 VDC</p> <p>OUTPUT SIGNAL (4 – 20) mA</p> <p>PROCESS CONNECTION: 1/2 " NPTF</p> <p>WITH ALL ACCESSORIES (CABLE GLAND 1/2 " NPT , 2" U – BOLT PIPE MOUNTING BRACKET)</p>	NOS	10
8	TRAINING THREE PERSON ONE WEEK IN MANUFACTURE WORKSHOP ,	LOT	1
	ORIGIN : USA , West Europe		