

SGC-C 58 -2011
Lathe Machine

تسلسل ITEM	المواصفات DESCRIPTION	الوحدة UNIT	الكمية المطلوبة REQ.QTY
	Center height 250 mm Center width 1000 mm Swing over bed 500 mm Swing over cross 300 mm Swing in gap 700 mm Width of bed 400mm Spindle hole 72 mm Number of Spindle speeds 21 Range of Spindle speeds 20-2000 r.p.m Travel of Tailstock Quill 220mm Range of Threads Metric 0.5-120mm Inch 60-1/4TPI Number of Feeds 120 each type Range of Longitudinal feeds 0.04-12mm/rev Range of Cross feeds 0.02-6mm/rev Motor 380 V - 3 ph -50 HZ <u>EXTENT OF SUPPLY</u> * 500mm Face plate * 140-280 Steady * 500mm 4 jaw Chuck * soft jaws for 250mm Chuck * Tapper Turning Attachment * 4- 5 MT Drill Sleeve * 1-16mm j3 keyed Drill Chuck * 4MT × J Drill Chuck Arbor * 5 MT Revolving centre *XL 3 Quick change tool post *set of 6 machine mounts-no 2 *9 pc 25mm index able Turn Tool set **Spare Parts For Two Years	NOS	2(TWO)

Notes:

- 1- The origin must be (JAPAN – UK – GERMANY)
- 2- Supply " origin certificate"
- 3- Supply third party inspection .
- 4- Supply catalogue with offer to explain the main parts for equipment, manner of automation and the maintenance . the offer consider not identical if don't supply it.
- 5- Training to three persons for seven days period in origin country.
- 6- Supply list for annex material with offer.
- 7- Supply spare parts for two years.
- 8- One year warranty